

View Online at <https://aerobasegroup.com/nsn/5935-01-359-4824>

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

32.5 millimeters

**Overall Diameter:**

Between 44.2 millimeters and 44.8 millimeters

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

**Distance From Mounting Shoulder To Front Face:**

22.6 millimeters

**Mounting Facility Thickness:**

Between 1.58 millimeters and 3.20 millimeters

**Threaded Device Type:**

Back shell and coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

23 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 50.0 and 160.0 and 190.0 and 225.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

7.11 millimeters and 0.428 inches and 7.8 millimeters

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

**Features Provided:**

Scoopproof design and color band engagement indicator

**Thready Qty Per Inch (tpi):**

10

**Thread Size:**

25.0 millimeters and 1.188 inches and 32.0 millimeters

**Thread Pitch In Millimeters:**

1.00

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic epoxy single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

21 single mating end 2nd contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.026 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Iso m and special acme and iso m

**Specification Data:**

81349-dod-c-38999/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

N/a

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.