## NSN 5935-01-359-5272

Electrical Receptacle Connector - Page 1 of 2

Qq-n-236 federal specification single material response



View Online at https://aerobasegroup.com/nsn/5935-01-359-5272

**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape spring mount **Overall Length:** Between 1.607 inches and 1.627 inches **Overall Diameter:** Between 1.235 inches and 1.255 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 3 number 16 single mating end **Contact Removability:** Removable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 12 **Thread Size:** 1.063 inches and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Steel single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Nickel alloy **Shell Material Specification:** 

## NSN 5935-01-359-5272

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:** Mil-m-14 military specification single material response single mating end **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold **Supplementary Features:** Mounting method - friction **Thread Series Designator:** Un Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.