
NSN 5935-01-359-8133

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Green **Body Style:** Threaded bushing mounted **Overall Length:** 1.000 inches Mounting Bushing Length: 0.250 inches **Body Length:** 0.840 inches **Overall Diameter:** 0.338 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.079 inches and 0.081 inches single finger **Finger Accommodation Length:** 0.438 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.260 inches **Current Rating In Amps:** 5.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Plastic polytetrafluoroethylene insulator **Precious Material And Location:** Contact and terminal surfaces gold

NSN 5935-01-359-8133

Tip Jack - Page 2 of 2



Precious Material:

Gold

Surface Treatment:

Nickel bushing

Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-39024/2 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400