## NSN 5935-01-359-8926

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-359-8926 **Body Style:** Right angle type **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.790 inches **Overall Width:** 0.590 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end **Terminal Type:** Printed circuit single mating end single contact grouping **Shell Material:** Metal **Shell Surface Treatment:** Cadmium

Included Contact Quantity:

50 single mating end single contact grouping

## NSN 5935-01-359-8926

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/23 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No