

View Online at <https://aerobasegroup.com/nsn/5935-01-360-1168>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated from panel

Identification Code Color:

Green

Body Style:

Threaded bushing mounted

Overall Length:

Between 0.650 inches and 0.750 inches

Mounting Bushing Length:

Between 0.430 inches and 0.500 inches

Body Length:

Between 0.650 inches and 0.750 inches

Overall Diameter:

Between 0.380 inches and 0.510 inches

Bushing Accommodation Hole Shape:

Round

Accommodated Finger Type:

Banana spring single finger

Finger Accommodation Diameter:

0.160 inches single finger and 0.170 inches single finger

Finger Accommodation Length:

0.562 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.250 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Terminal Type:

Eyelet w/tab

Material:

Plastic, polyamide insulator

Material:

Plastic polyamide insulator

Precious Material And Location:

Spring contact and terminal surfaces gold

Precious Material:

Gold

Surface Treatment:

Gold terminal

Surface Treatment:

Gold spring

Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-39024/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400