

View Online at <https://aerobasegroup.com/nsn/5935-01-360-1169>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Blue

Body Style:

Threaded bushing mounted

Overall Length:

Between 0.650 inches and 0.750 inches

Mounting Bushing Length:

0.500 inches

Body Length:

0.580 inches

Overall Diameter:

Between 0.380 inches and 0.510 inches

Accommodated Finger Type:

Banana spring single finger

Finger Accommodation Diameter:

0.160 inches single finger and 0.180 inches single finger

Finger Accommodation Length:

0.438 inches single finger

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Terminal Type:

Eyelet w/tab

Material:

Plastic, polytetrafluoroethylene body

Material:

Plastic polytetrafluoroethylene insulator

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Nickel bushing

Surface Treatment:

Nickel bushing

Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-39024/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03400