

View Online at <https://aerobasegroup.com/nsn/5935-01-360-1169>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Blue

**Body Style:**

Threaded bushing mounted

**Overall Length:**

Between 0.650 inches and 0.750 inches

**Mounting Bushing Length:**

0.500 inches

**Body Length:**

0.580 inches

**Overall Diameter:**

Between 0.380 inches and 0.510 inches

**Accommodated Finger Type:**

Banana spring single finger

**Finger Accommodation Diameter:**

0.160 inches single finger and 0.180 inches single finger

**Finger Accommodation Length:**

0.438 inches single finger

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

1 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Type:**

Eyelet w/tab

**Material:**

Plastic, polytetrafluoroethylene body

**Material:**

Plastic polytetrafluoroethylene insulator

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Surface Treatment:**

Nickel bushing

**Surface Treatment:**

Nickel bushing

**Test Data Document:**

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-39024/19 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03400