NSN 5935-01-360-2327

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-360-2327 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/solder mount **Overall Length:** 1.250 inches **Overall Diameter:** Between 1.431 inches and 1.437 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 120.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 12 Thread Size: 1.188 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Steel single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Glass single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

NSN 5935-01-360-2327

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel comp 316
Shell Material Specification:
Qq-s-763 federal specification single material response
Included Contact Quantity:
1 single mating end 1st contact grouping14 single mating end 2nd contact grouping15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - welded
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.
WIII-g-452U4 spec.