NSN 5935-01-360-3985

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-360-3985

Body Style:
Straight shape
Overall Length:
8.820 inches
Overall Height:
0.695 inches
Overall Width:
0.500 inches
Unthreaded Mounting Hole Diameter:
Between 0.130 inches and 0.136 inches
Distance Between Mounting Facility Centers:
8.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
4 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy 260 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c or d, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290
cl 2 federal specification 2nd treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Solder stud single mating end single contact grouping
Contact Material Specification:
Qq-b-613 federal specification single material response single mating end single contact grouping
Shell Material:

Chromate

Aluminum alloy 6061

Shell Surface Treatment:

NSN 5935-01-360-3985

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Mil-c-5541, cl 1 military specification single treatment response

Shell Material Specification:

Qq-a-200/8, t6 federal specification single material response

Insert Material Specification:

Astm d4066 assn standard single material response single mating end

Included Contact Quantity:

304 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Grounding bushing located at positions a5 and d75

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.304 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.