NSN 5935-01-360-6602

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-360-6602

View Online at https://aerobasegroup.com/nsn/5935-01-360-6602
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.500 inches
Overall Diameter:
1.183 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant
Cable Entrance Diameter:
Between 0.416 inches and 0.539 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-15 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet slot
Connector Cable Strain Relief Method:
Cable clamp
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-01-360-6602

Electrical Plug Connector - Page 2 of 2



Ind	clud	led	Con	tact	Qua	ntity:
	JIUU	ıcu	CULI	ιαυι	wua	HILLLY.

1 single mating end 1st contact grouping14 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.019 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms3116 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.