NSN 5935-01-360-6605



Receptacle Dummy Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-360-6605 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 23.4 millimeters **Overall Height:** Between 30.7 millimeters and 31.3 millimeters **Overall Width:** Between 30.7 millimeters and 31.3 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 23.01 millimeters and 24.61 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 23.01 millimeters and 24.61 millimeters **Distance From Mounting Shoulder To Front Face:** Between 20.9 millimeters and 21.4 millimeters **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 1.000 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Test Data Document:** 81349-mil-c-38999/22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-3999/22 professional/industrial association specification

NSN 5935-01-360-6605

Receptacle Dummy Connector - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0