## NSN 5935-01-361-0408

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-361-0408 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/jackscrew **Overall Length:** 2.148 inches **Overall Height:** 2.840 inches **Overall Width:** 0.725 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** 2.460 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 88 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Polarization boss Shell Type: Solid **Connector Locking Method:** Jackscrew **Operating Tempurature Rating:** Between -54.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping

**Contact Material:** Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

## NSN 5935-01-361-0408

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate glass filled single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Included Contact Quantity:
88 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.088 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0