

View Online at <https://aerobasegroup.com/nsn/5935-01-361-4311>

Body Style:

Angle shape, pcb type

Overall Length:

5.530 inches

Overall Height:

0.705 inches

Overall Width:

0.395 inches

Environmental Protection:

Corrosion resistant and vibration resistant and shock resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.103 inches and 0.107 inches

Distance Between Mounting Facility Centers:

5.300 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-b-613 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Astm d-4066 assn standard single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.