# NSN 5935-01-361-5363

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-361-5363 **Thread Class:** 2b **Thread Direction:** Right-hand **Overall Length:** Between 3.000 inches and 3.030 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 2.570 inches and 2.580 inches **Overall Width:** Between 1.146 inches and 1.170 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.558 inches and 0.566 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 32 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): **Thread Size:** 0.138 inches **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Nickel

# NSN 5935-01-361-5363

Receptacle Dummy Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response

# **Shell Material Specification:**

Qq-a-591 federal specification single material response

# **Included Contact Quantity:**

32 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.032 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.