NSN 5935-01-361-5366

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-361-5366

2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.284 inches **Overall Diameter:** Between 2.172 inches and 2.204 inches **Distance From Mounting Shoulder To Front Face:** Between 1.085 inches and 1.095 inches **Mounting Facility Thickness:** Between 0.125 inches and 0.300 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 95.0 and 132.0 and 232.0 and 260.0 and 345.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.438 inches and 1.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Crimp single mating end single contact grouping

NSN 5935-01-361-5366

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 128 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round w/flat |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.128 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |