NSN 5935-01-361-5370

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-361-5370 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.465 inches **Overall Height:** 1.688 inches **Overall Width:** 1.688 inches **Unthreaded Mounting Hole Diameter:** 0.150 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.297 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.297 inches **Distance From Mounting Shoulder To Front Face:** Between 0.556 inches and 0.587 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 20-41 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.188 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-361-5370

Electrical Receptacle Connector - Page 2 of 2



| Contact Surface Treatment: |
|---|
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy 6061 or aluminum alloy 380.0 and aluminum alloy a380.0 |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 41 single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.041 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-c-26482 spec. |
| |