NSN 5935-01-361-6305

Electrical Receptacle Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-361-6305 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.775 inches |
| Overall Height: |
| Between 5.150 inches and 5.170 inches |
| Overall Width: |
| Between 4.980 inches and 5.010 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.146 inches and 0.156 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 4.728 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 4.550 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.115 inches and 0.135 inches |
| Mating End Quantity: |
| 6 |
| Polarization Method: |
| Guide pin/socket and 3 polarization posts |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Insert Material: |
| Plastic diallyl phthalate glass filled all mating ends or plastic polyester glass filled all mating ends |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Shell Surface Treatment Specification: |
| Qq-p-416, type ii federal specification all treatment responses |
| Shell Material Specification: |
| Qq-a-250 federal specification single material response or qq-a-367 federal specification single material response or qq-a-591 federal |
| specification single material response |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification 1st material response all mating ends or mil-m-24519 military specification 2nd material response |
| all mating ends |

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5935-01-361-6305

Electrical Receptacle Connector Body - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.