NSN 5935-01-361-6646

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-361-6646

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.841 inches
Overall Diameter:
2.344 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-22 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
16 and 10
Thread Size:
1.875 inches and 2.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic single mating end

Terminal Type:

Solder well single mating end all contact groupings

NSN 5935-01-361-6646Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Oxide
Included Contact Quantity:
3 single mating end 1st contact grouping3 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.030 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Un and double stub
Specification Data:
96906-ms17344 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-22992 spec.