

View Online at <https://aerobasegroup.com/nsn/5935-01-361-7129>

**Body Style:**

Straight shape, rectangular

**Overall Length:**

Between 2.032 inches and 2.062 inches

**Overall Height:**

1.541 inches

**Overall Width:**

Between 1.612 inches and 1.619 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.118 inches and 0.122 inches

**Distance Between Mounting Facility Centers:**

Between 1.161 inches and 1.173 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32c2 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic epoxy single mating end or plastic phenolic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

**Insert Material Specification:**

Mil-m-14, ty gdi-30f or sdg-f military specification 1st material response single mating end or allied chemical 1288 bx mfr ref 2nd material response single mating end or mil-m-14 military specification 3rd material response single mating end

**Included Contact Quantity:**

2 single mating end 1st contact grouping 30 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.040 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.