

View Online at <https://aerobasegroup.com/nsn/5935-01-362-6304>

**Body Style:**

Right angle type

**Overall Length:**

4.800 inches

**Overall Width:**

0.325 inches

**Body Height:**

0.238 inches

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:**

98 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.098 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-55302/128 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-55302 spec.