NSN 5935-01-363-1017

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-1017

Thread Class:
2a and 2b and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape, angle
Overall Length:
0.935 inches
Overall Height:
0.308 inches
Overall Width:
0.420 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.091 inches and 0.101 inches
Distance Between Mounting Facility Centers:
Between 0.710 inches and 0.720 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Side single mating end single contact grouping

NSN 5935-01-363-1017

Electrical Receptacle Connector - Page 2 of 2



I	r	١	S	ρ	r	ŧ	ı	V	la	ıt	ρ	r	i	а	ı	•
ı		ı	J	c		L	•	ш	C	ľ	c		ı	а	ı	

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp and solder single mating end single contact grouping

Shell Material:

Aluminum or aluminum alloy or aluminum alloy 380.0

Shell Surface Treatment:

Nickel

Shell Material Specification:

Qq-a-200/8 federal specification single material response or qq-250/11 federal specification single material response or qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Pcb terminals 0.109 in. Lg

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.