NSN 5935-01-363-1058

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-1058 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.887 inches **Overall Diameter:** Between 1.484 inches and 1.516 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant **Distance From Mounting Shoulder To Front Face:** Between 0.680 inches and 0.712 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.124 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 120.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.125 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-363-1058

Electrical Receptacle Connector - Page 2 of 2



| Contact Material: |
|--|
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 26 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| S S |
| 0.026 gold grains, troy |
| |
| 0.026 gold grains, troy |
| 0.026 gold grains, troy Precious Material: |
| 0.026 gold grains, troy Precious Material: Gold |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: Unef |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: Unef Shelf Life: |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: Unef Shelf Life: N/a |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: Unef Shelf Life: N/a |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: |
| 0.026 gold grains, troy Precious Material: Gold Supplementary Features: Mounting method - bushing Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: |