## NSN 5935-01-363-3291

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-3291

view offilite at https://defobasegroup.com/hsh/osos-01-505-5251
Body Style:
Straight shape
Overall Length:
3.650 inches
Overall Height:
0.637 inches
Overall Width:
0.250 inches
Environmental Protection:
Vibration resistant and solvent resistant and salt spray proof
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyphenylene single mating end
Terminal Type:
Pin single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdgf military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response
single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
66 single mating end single contact grouping
Included Contact Type:

Contact surfaces gold

**Precious Material And Location:** 

D-socket single mating end single contact grouping

## NSN 5935-01-363-3291

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.066 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.