

View Online at <https://aerobasegroup.com/nsn/5935-01-363-6592>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Environmental Protection:**

Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.093 inches and 0.099 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell and friction

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thread Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Round socket 1st mating end single contact grouping

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0