NSN 5935-01-363-7023

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-7023

Body Style:
Right angle type
Overall Length:
3.340 inches
Overall Height:
0.263 inches
Overall Width:
0.580 inches
Environmental Protection:
Thermal shock resistant and salt water resistant and humidity resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.097 inches
Distance Between Mounting Facility Centers:
3.140 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:

moradea comact quantity.

56 single mating end single contact grouping

NSN 5935-01-363-7023

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.056 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0