NSN 5935-01-363-7292

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-7292 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.400 inches **Overall Height:** Between 0.745 inches and 0.755 inches **Overall Width:** Between 0.375 inches and 0.385 inches **Environmental Protection:** Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant **Distance Between Mounting Facility Centers:** 0.560 inches **Distance From Mounting Shoulder To Front Face:** Between 0.122 inches and 0.128 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:**

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Snap ring

Connector Cable Strain Relief Method:

Shrinkable tubing

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-363-7292

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Shell Material Specification:
Qq-p-35 federal specification single material response
Insert Material Specification:
L-p-389 federal specification single material response single mating end or l-p-403 federal specification single material response single
mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-g-45204 spec.

A039b0