Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-8485

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.950 inches
Overall Height:
0.620 inches
Overall Width:
Between 0.360 inches and 0.380 inches
Distance Between Mounting Facility Centers:
0.481 inches
Cable Entrance Diameter:
Between 0.141 inches and 0.155 inches
Distance From Mounting Shoulder To Front Face:
Between 0.310 inches and 0.420 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

## NSN 5935-01-363-8485 Electrical Receptacle Connector - Page 2 of 2



**Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Included Contact Quantity:** 1 single mating end single contact grouping Included Contact Type: Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0