## NSN 5935-01-363-9498

Thread Class: 2a and 2b

grouping

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-363-9498

Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.468 inches
Overall Diameter:
0.995 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
12s-3 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
70.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thready Qty Per Inch (tpi):
24 and 20
Thread Size:
0.625 inches and 0.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping or silver single mating end single contact

## **NSN 5935-01-363-9498**Electrical Plug Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver or contact surfaces silver
Precious Material And Weight:
$0.002 \ \text{gold}$ grains, troy and $0.002 \ \text{silver}$ grains, troy or $0.002 \ \text{silver}$ grains, troy
Precious Material:
Gold and silver or silver
Gold and silver or silver  Thread Series Designator:
Thread Series Designator:
Thread Series Designator: Unef and unef
Thread Series Designator: Unef and unef Shelf Life:
Thread Series Designator: Unef and unef Shelf Life: N/a
Thread Series Designator: Unef and unef Shelf Life: N/a
Thread Series Designator: Unef and unef Shelf Life: N/a Unit Of Measure:
Thread Series Designator: Unef and unef Shelf Life: N/a Unit Of Measure: Demilitarization:
Thread Series Designator: Unef and unef Shelf Life: N/a Unit Of Measure: Demilitarization: No
Thread Series Designator: Unef and unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: