## NSN 5935-01-364-1190

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-364-1190

view Offiline at https://defobasegroup.com/nsi//0900-01-004-1190
Body Style:
Straight shape
Overall Length:
2.095 inches
Overall Height:
0.656 inches
Overall Width:
0.420 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Saraulaak kit aanarata

Contact surfaces gold

**Precious Material And Location:** 

## NSN 5935-01-364-1190

Electrical Receptacle Connector - Page 2 of 2



	Pr	ecious	Material	And	Weight:
--	----	--------	----------	-----	---------

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0