NSN 5935-01-364-2573

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-364-2573

Body Style:
Straight shape
Overall Length:
2.140 inches
Overall Diameter:
0.440 inches
Cable Entrance Diameter:
0.242 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Push-pull
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
Digital group multiplexer, an/trc-138, -173, -174, -175
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy

NSN 5935-01-364-2573

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204 military specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.