## NSN 5935-01-364-2579

Connector Adapter - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5955-01-564-2579
Body Style:
Straight shape, external/internal coupling
Overall Diameter:
1.270 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant
Mating End Quantity:
2
Contact Position Arrangement Style:
14-19 all mating ends
Contact Removability:
Removable all mating ends all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin and bayonet slot
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings and nickel all mating ends all contact groupings
Insert Material:
Plastic all mating ends
Shell Material:
Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0
Shell Surface Treatment:
Nickel
Included Contact Quantity:
19 1st mating end single contact grouping19 2nd mating end single contact grouping
Included Contact Type:
Round pin 1st mating end single contact groupinground socket 2nd mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.038 gold grains, troy
Precious Material:
Gold
Shelf Life:

N/a

## NSN 5935-01-364-2579

Connector Adapter - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A039b0