NSN 5935-01-364-7760

Crimp single mating end single contact grouping

Insert Material Specification:

end

Body Style:

Overall Length:

Straight shape, external coupling

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-364-7760

1.080 inches
Overall Height:
0.375 inches
Overall Width:
0.375 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.232 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.232 inches
Distance From Mounting Shoulder To Front Face:
0.250 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Rf single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Push-pull
End Application:
5895-01-168-7286 interrogator set
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:

L-p-389 federal specification 1st material response single mating end or I-p-403 federal specification 2nd material response single mating

NSN 5935-01-364-7760

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantit	ty:
--------------------------	-----

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.