

View Online at <https://aerobasegroup.com/nsn/5935-01-364-7760>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.080 inches

**Overall Height:**

0.375 inches

**Overall Width:**

0.375 inches

**Unthreaded Mounting Hole Diameter:**

0.093 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.232 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.232 inches

**Distance From Mounting Shoulder To Front Face:**

0.250 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Rf single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Push-pull

**End Application:**

5895-01-168-7286 interrogator set

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Insert Material Specification:**

L-p-389 federal specification 1st material response single mating end or l-p-403 federal specification 2nd material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.