NSN 5935-01-364-9201



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-364-9201 **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 34.16 millimeters **Overall Diameter:** Between 37.6 millimeters and 38.6 millimeters **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 27.5 millimeters and 28.4 millimeters **Mounting Facility Thickness:** Between 1.5 millimeters and 3.2 millimeters **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Afdx 11-5 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 90.0 and 270.0 Shell Type: Solid **Connector Locking Method:** Detent **Thread Size:** 25.0 millimeters

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-364-9201

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6h external
Included Contact Quantity:
5 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m
Specification Data:
81349-mil-c-38999/44 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0