NSN 5935-01-364-9213

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-364-9213

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
1.335 inches
Overall Height:
0.419 inches
Overall Width:
0.800 inches
Distance Between Mounting Facility Centers:
Between 1.110 inches and 1.120 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
4 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Post jacksocket
Solid Connector Locking Method: Post jacksocket Thread Size:
Solid Connector Locking Method: Post jacksocket Thread Size: 0.086 inches
Solid Connector Locking Method: Post jacksocket Thread Size: 0.086 inches Terminal Location:
Solid Connector Locking Method: Post jacksocket Thread Size: 0.086 inches Terminal Location: Side single mating end single contact grouping
Solid Connector Locking Method: Post jacksocket Thread Size: 0.086 inches Terminal Location: Side single mating end single contact grouping Contact Material:
Connector Locking Method: Post jacksocket Thread Size: 0.086 inches Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Post jacksocket Thread Size: 0.086 inches Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-364-9213

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
31 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.031 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.