

View Online at <https://aerobasegroup.com/nsn/5935-01-365-0486>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

34.16 millimeters

Overall Height:

Between 45.5 millimeters and 46.6 millimeters

Overall Width:

Between 45.5 millimeters and 46.6 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 3.6 millimeters and 4.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

38.1 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 45.5 millimeters and 46.6 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.2 millimeters and 20.8 millimeters

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

25-24 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 100.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Detent

Operating Temperature Rating:

Between -65.0 degrees celsius and 176.0 degrees celsius

Thread Size:

37.0 millimeters

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Thread Tolerance Class:

6h external

Included Contact Quantity:

12 single mating end 1st contact grouping 12 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.024 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m

Specification Data:

81349-mil-c-38999/40 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0