

View Online at <https://aerobasegroup.com/nsn/5935-01-365-5913>

Thread Class:

2a and 2a and 2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

2.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.460 inches

Overall Height:

1.449 inches

Overall Width:

0.725 inches

Environmental Protection:

Moisture resistant and moisture proof and salt water resistant and shock proof and vibration proof and fungus resistant and thermal shock resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

15

Contact Position Arrangement Style:

88 single mating end

Polarization Method:

Polarization boss and guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Jackscrew

Thread Size:

0.138 inches and 0.138 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic epoxy single mating end or plastic phenolic single mating end

Shell Material:

Steel comp 302 or steel comp 303 or steel comp 304

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-s-766 federal specification single material response

Insert Material Specification:

Mil-m-14, sgd-f military specification single material response single mating end or mil-p-19833, gdi-30f military specification single material response single mating end

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.