## NSN 5935-01-366-0013

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-366-0013 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape, pcb type **Overall Length:** 0.785 inches **Overall Height:** 0.800 inches **Overall Width:** 0.310 inches **Distance Between Mounting Facility Centers:** 0.565 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Post jacksocket **Thread Size:** 0.086 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end

**Terminal Type:** 

Wire wrap single mating end single contact grouping

## NSN 5935-01-366-0013

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy or steel
Shell Surface Treatment:
Nickel or passivate
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0