## NSN 5935-01-366-0022

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-366-0022

**Body Style:** 

Rectangular shape center screwlock

**Overall Length:** 

Between 2.115 inches and 2.135 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.745 inches and 1.755 inches

**Overall Height:** 

1.860 inches

**Overall Width:** 

Between 0.820 inches and 0.840 inches

**Environmental Protection:** 

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.143 inches and 0.155 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

36 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Included Contact Quantity:** 

36 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

Jackscrew type-male and location-center

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-366-0022

Electrical Receptacle Connector - Page 2 of 2



recious	Material	And	Weight:
---------	----------	-----	---------

0.036 gold grains, troy

**Precious Material:** 

Gold

## **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-28748/10 professional/industrial association specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0