NSN 5935-01-366-6863

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-366-6863

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.220 inches |
| Overall Diameter: |
| 1.890 inches |
| Threaded Device Type: |
| Back shell and coupling facility |
| Mating End Quantity: |
| 1 |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 80.0 and 142.0 and 196.0 and 293.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thread Size: |
| 37.0 millimeters and 1.625 inches |
| Terminal Location: |
| Back single mating end 1st contact groupingback single mating end 2nd contact grouping |
| Contact Material: |
| Copper alloy single mating end 1st contact groupingcopper alloy single mating end 2nd contact grouping |
| Contact Surface Treatment: |
| Gold single mating end 1st contact groupinggold single mating end 2nd contact grouping |
| Insert Material: |
| Plastic epoxy single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Thread Tolerance Class: |
| 6g external |
| Included Contact Quantity: |
| 2 single mating end 1st contact grouping97 single mating end 2nd contact grouping |
| Included Contact Type: |

Included Contact Type:

Coaxial pin single mating end 1st contact groupinground pin single mating end 2nd contact grouping

NSN 5935-01-366-6863

Electrical Plug Connector - Page 2 of 2



| Precious Material And Location: |
|---------------------------------|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.099 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Iso m and special acme |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A039b0