NSN 5935-01-366-7905

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-366-7905

Body Style:

Straight shape, flush mount

Overall Length:

1.385 inches

Overall Height:

1.170 inches

Overall Width:

3.028 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.282 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.578 inches

Distance From Mounting Shoulder To Front Face:

0.526 inches

Mating End Quantity:

.

Contact Position Arrangement Style:

32 single mating end

Contact Removability:

Removable single mating end single contact grouping

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-366-7905

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification: Qq-a-591 federal specification single material response **Included Contact Quantity:** 32 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Furnished items - spare contact **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.034 gold grains, troy **Precious Material:** Gold **Supplementary Features:** Mounting method - unthreaded hole **Specification Data:** 81349-mil-c-83733/01 government specification **Specification Or Standard:** 81349--83733/01 specification sheet Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.