NSN 5935-01-367-8668

Body Style:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-367-8668

Appliance		
Overall Length:		
79.0 millimeters		
Overall Height:		
26.4 millimeters		
Overall Width:		
18.4 millimeters		
Cable Entrance Diameter:		
7.6 millimeters		
Mating End Quantity:		
1		
Contact Position Arrangement Style:		
3 single mating end		
Contact Removability:		
Removable single mating end single contact grouping		
Contact Maximum Current Rating In Amps:		
6.0 single mating end single contact grouping		
Contact Maximum Ac Voltage Rating In Volts:		
250.0 single mating end single contact grouping		
Polarization Method:		
Contact		
Contact Shell Type:		
Shell Type:		
Shell Type: Split		
Shell Type: Split Connector Locking Method:		
Shell Type: Split Connector Locking Method: Friction		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method:		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating:		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location:		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Nickel single mating end single contact grouping		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Nickel single mating end single contact grouping Terminal Type:		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Nickel single mating end single contact grouping Terminal Type: Screw single mating end single contact grouping		
Shell Type: Split Connector Locking Method: Friction Connector Cable Strain Relief Method: Crimp type Operating Tempurature Rating: Between -40.0 degrees celsius and 70.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Nickel single mating end single contact grouping Terminal Type: Screw single mating end single contact grouping Shell Material:		

NSN 5935-01-367-8668

Electrical Plug Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Flat socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0