NSN 5935-01-368-9627

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-368-9627

2a and 2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
2.350 inches
Overall Height:
0.525 inches
Overall Width:
0.422 inches
Environmental Protection:
Vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.121 inches
Distance Between Mounting Facility Centers:
2.100 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Contact Carrace Treatment

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-368-9627

Electrical Receptacle Connector - Page 2 of 2



	11010	:	
Insert	IVIATE	er iai	G

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-g-45204, ty2, grade c, class 1 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-female and location-left handandjackscrew type-male and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.