## NSN 5935-01-368-9629

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-368-9629 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.700 inches **Overall Diameter:** 1.750 inches **Environmental Protection:** Corrosion resistant and moisture resistant **Distance From Mounting Shoulder To Front Face:** 1.010 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Mounting bushing **Board Accommodated Width:** 0.250 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-14 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 

1.250 inches **Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-01-368-9629

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 14 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Round pin single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0