## NSN 5935-01-369-0801

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-0801

**Body Style:** 

Straight shape

**Overall Length:** 

Between 3.960 inches and 3.965 inches

**Overall Height:** 

0.700 inches

**Overall Width:** 

0.250 inches

**Unthreaded Mounting Hole Diameter:** 

0.093 inches and 0.187 inches

**Distance Between Mounting Facility Centers:** 

3.700 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

128 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

**Included Contact Quantity:** 

128 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.128 gold grains, troy

**Precious Material:** 

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5935-01-369-0801

Electrical Receptacle Connector - Page 2 of 2



Specification Data:
8134955302/121-01 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.