## NSN 5935-01-369-0805

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-0805 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.055 inches **Bushing Diameter:** 0.688 inches **Distance From Mounting Shoulder To Front Face:** 0.308 inches **Mounting Facility Thickness:** 0.200 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded coupling ring Width Across Flats: 0.563 inches Thready Qty Per Inch (tpi): 32 and 28 **Thread Size:** 0.375 inches and 0.562 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-01-369-0805

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel and copper
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Triaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0