NSN 5935-01-369-2310

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-2310 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.625 inches **Overall Height:** 0.823 inches **Overall Width:** 0.260 inches **Unthreaded Mounting Hole Diameter:** Between 0.101 inches and 0.106 inches **Distance Between Mounting Facility Centers:** 0.481 inches **Distance From Mounting Shoulder To Front Face:** 0.463 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-369-2310

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0