NSN 5935-01-369-5688

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-5688
Thread Class:
2b and 2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.180 inches
Overall Diameter:
1.375 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and vibration proof
Threaded Device Type:
Coupling facility and back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
Bhba 18-31 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0 and 105.0 and 140.0 and 215.0 and 265.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thread Size:

1.0625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-369-5688Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
31 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.031 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
8134983723/96w1831n government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-83723 spec.