NSN 5935-01-369-5689

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-5689

Thread Class:

2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.053 inches **Overall Diameter:** 0.430 inches **Cable Entrance Diameter:** 0.350 inches **Distance From Mounting Shoulder To Front Face:** 0.712 inches **Mounting Facility Thickness:** 0.093 inches **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Shrinkable tubing **Cable Opening Length:** 1.750 inches **Thread Size:** 0.3125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Nickel single mating end single contact grouping and gold single mating end single contact grouping **Insert Material:** Plastic polyester single mating end **Terminal Type:**

Solder well single mating end single contact grouping

NSN 5935-01-369-5689

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Triaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.004 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - jam mut
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0