## NSN 5935-01-369-6726

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-369-6726 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, pcb type **Overall Length:** 1.250 inches **Overall Height:** 0.620 inches **Overall Width:** 0.280 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thread Size: Copper alloy single mating end single contact grouping

0.086 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material: Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Terminal Type:** Printed circuit single mating end single contact grouping **Unable To Decode:** 

Unable to decode and unable to decode

## NSN 5935-01-369-6726

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 26 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Furnished items - bracket **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.026 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0